

LORD Duct Tape

Product Description

LORD Duct Tape based on polyethylene and cloth composite materials, coated with rubber/hotmelt adhesive. It has strong stripping force, force, tack, tensile strength, which can withstand oil wax, aging, leak-proof, waterproof, corrosion -proof, insulated and essay to tear. It is a strong adhesive tape with different colors for separation.


Application

LORD Duct tape is widely used to seal heavy packing cartons, books backing: fix carpet seams, suture pipeline: repair mains connector, penetrated parts: fix the protective pad on the floor, counter top and wall. It is also applying to bundle, fix, lap, patch in the industry and any other temporary fixed locations.

Technical Data

Model Number	Mesh Density	Adhesive Type	Thickness	Initial tack	Holding Power	180° Adhesion to steel	Tensile Strength
DCT 150	27 Mesh	Water Acrylic/Hotmelt	0.15±0.01	8	8	5.8	50
DCT 170	35 Mesh	Water Acrylic/Hotmelt	0.17±0.01	8	8	7	55
DCT 220	70 Mesh	Water Acrylic/Hotmelt	0.22±0.01	12	12	9	60
DCT 230-R	50 Mesh	Water Acrylic/Hotmelt	0.23±0.01	15	15	10	75
DCT 280-Printed	70 Mesh	Water Acrylic/Hotmelt	0.28±0.01	10	19	10	150

Rolls widths/lengths available on request.



LORD®