



LOUIS ADHESIVE TAPES CO., LTD.

1070 Soi Suanplu, South Sathorn Rd., Bangkok 10120 Thailand

Tel : (662) 2872100 (12 Lines), 2864223-6, 2874326-8

Fax : (662) 2871101 (direct), 2874736

E-mail : export@louistapes.com URL : www.louistapes.com



Masking Tape

High quality crepe paper coated with natural rubber-based adhesive. The tape is conformable to irregular surfaces with excellent adhesion property. Suitable for masking, sealing or use as surface protection.

Features

- Strong, high quality crepe paper coated with natural rubber-based adhesive.
- Excellent adhesive coating, quick and easy to unwind.
- Heat resistance up to 120°C for 1 hour and up to 130°C for 30 minutes.
- Conformable to irregular surfaces.
- No adhesive residue after removal.

Applications

- Ideal for artistic work, masking, sealing, bundling, and light packaging.
- Recommended for temporary surface protection of electrical appliances and machinery parts.

Code No.	Adhesive	Thickness	Length	Core Size	Application	Temperature
M267	Rubber Solvent Adhesive	150µ ±10%	18,36 and 50M	3 inches	Industrial	120°C for 1 hour
M266		145µ ±10%			Automotive	
209		140µ ±10%				
M246		135µ ±10%				
M358		140µ ±10%				General purpose
M355		130µ ±10%			120°C for 1 hour	
M245		130µ ±10%				
M244		125µ ±10%				

*Custom sizes available upon request